

GigBAR Bridge ILS

Enjoy a customizable party lighting setup that suits your needs with the connectable GigBAR Bridge ILS. This 2-in-1 lighting system has a minimal setup time thanks to its moving heads and wash lights that come pre-mounted onto a single bar. ILS compatibility makes creating coordinated light shows with this unit and different fixture types easy as 1, 2, 3. Create dynamic dancefloor moments with just one system.

HIGHLIGHTS

- 2-in-1 lighting system that includes moving heads and washes pre-mounted on a single bar
- Quickly and securely connect multiple fixtures with the built-in locking system
- Built-in DFI transceiver communicates DMX or ILS signals wirelessly
- Safely mounts onto truss or mobile tripods using the removable bracket
- Easy navigation and access all functions directly from the full-color LCD display
- Powerful moving heads with separate color and gobo wheels allow for creative programming
- Totem Mode keeps the moving heads focused on the dance floor
- Save time running cables and extension cords by power linking multiple units
- ILS compatibility for use in the ILS ecosystem
- Use the included RF remote to trigger the built-in shows without needing line of sight



SPECIFICATIONS

- DMX Channels : 3, 16 or 46
- DMX Connectors : 3-pin XLR
- Strobe Rate : 0 to 20Hz
- Operating Frequency : 2.4 GHZ
- Power Linking : 8 units @ 120 V; 13 units @ 230 V
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Weight : 18.6 lbs (8.4 kg)
- Size : 26 x 2.8 x 12 in (660 x 71 x 305 mm)
- Approvals : CE, RoHS , FCC
- Colors (moving head) : 9 + open, split colors, continuous scroll at variable speeds
- Gobos (moving head) : 9 + open, continuous scroll at variable speeds
- Light Source (moving head) : 1 LED (cool white) 40W (3A), 50,000 hours life expectancy.
- Light Source (wash) : 4 LEDs (hex-color RGBAW + UV) 10W (1.3 A), 50,000 hours life expectancy.
- Beam Angle (wash) : 22°
- Field Angle (wash) : 38°
- Power and Current : 191 W, 1.5 A @ 120 VAC, 60Hz
- Power and Current : 175 W, 1 A @ 230 VAC, 50Hz
- Fits Tripod Sizes : 1.5 in (37.4 mm)
- Max Unobstructed Distance (D-Fi) : 600 ft (183 m)
- Optional Controllers : RF, Footswitch, ILS Command
- Illuminance (moving head) : 6,594 Lux @ 2 m (per head)
- Illuminance (wash) : 375 lux @ 2 m (per section)

WHAT'S INCLUDED

- GigBAR Bridge ILS
- Power cable
- 2 Hanging brackets
- RF Remote
- Quick Reference Guide