

EVE P-160 RGBW

When warm, bright, even wash light is needed for mobile and installation applications, EVE P-160 RGBW delivers. This robust light boasts 160 total watts of red, green, blue and white LEDs for full color output as well as preset white color temperatures that are built right in. EVE P-160 RGBW includes interchangeable magnetic lenses to alter the beam to desired angles and a built-in gel frame holder and 6¼-inch accessory slot to hold barn doors. Streaming and video applications? EVE P-160 RGBW is the perfect solution. It features high-frequency LED dimming for flicker-free operation on camera. Its fanless design ensures 100% silent operation great for quiet stage and studio needs. [D-Fi USB](#) compatibility is on board for wireless master/slave or DMX control. EVE P-160 RGBW is tough and road-ready with a cast aluminum housing that provides extra strength without the weight and powerCON®-compatible power input/output connections for power linking.



HIGHLIGHTS

- Robust wash light designed for mobile and installation applications
- Included interchangeable magnetic lenses alter the beam to desired angles
- Full color output as well as preset white color temperatures built in.
- Built-in gel frame holder and 6¼-inch accessory slot to hold barn doors
- Fanless design ensures 100% silent operation
- Flicker-free on video due to the high-frequency LED dimming
- D-Fi USB compatibility for wireless master/slave or DMX control
- Cast aluminum housing provides extra strength without the weight
- powerCON®-compatible power input/output connections for power linking
- Fits best in the CHS-40 VIP gear bag

SPECIFICATIONS

- DMX Channels : 4, 6 or 11
- DMX Connectors : 3- and 5-pin XLR
- Light Source : 61 LEDs (14 red, 13 green, 14 blue, 20 white) 160 W total, (3.8 A), 50,000 hours life expectancy
- Strobe Rate : 0 to 33 Hz
- PWM Frequency : 25 kHz
- Beam Angle : 23°, 35° or 48°
- Field Angle : 50°, 63° or 85°
- Illuminance : (23°): 3,442 lux @ 2 m (no lens)
(35°): 2,414 lux @ 2 m (lens 1)
(48°): 1,310 lux @ 2 m (lens 2)
(23°): 519 lux @ 5 m (no lens)
(35°): 386 lux @ 5 m (lens 1)
(48°): 211 lux @ 5 m (lens 2)
- Lumens : 4,880
- Power Linking : 11 units @ 120 V; 21 units @ 230 V
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current : 122 W, 1 A @ 120 V, 60 Hz
121 W, 0.5 A @ 230 V, 50 Hz
- Weight : 7.8 lbs (3.6 kg)
- Size : 8.6 x 9.7 x 12 in (220 x 245 x 305 mm)
- Approvals : CE, MET, RoHS
- Accessory Holder/Gel Frame Size : 6.25 in (159 mm)
- CRI : 80 (Warm White)
- Color Temperature Range : 2700 to 6500 K
- Optional Controllers : DFI USB

WHAT'S INCLUDED

- EVE P-160 RGBW
- Power cord
- 2 lenses
- Gel frame
- Quick Reference Guide